

Conveyorized derinding machine
SKINNY II



DERINDING



MAJA[®]

Skinny II

Technical details

Type	Cutting width mm	Width of machine incl. operating lever mm	Depth with slide sheet mm	Height of machine mm	Electrical connection kW 3AC/50Hz/400V	Weight kg
Skinny II	434	809	1368	1205	0,75	190



Being the smallest of all MAJA derinding machines, the Skinny II is the most appreciated starter model for butcheries. It corresponds to the CE regulations concerning hygiene and operator safety and enables versatile use:

It can be used for automatic derinding of all flat pieces of meat, which are introduced into the machine through an infeed conveyor belt.

Round pieces of meat (shoulder, ham, pigs' knuckles) can be manually derinded in open version.



TECHNOLOGY FOR THE FUTURE

Equipment & features

- Quick conversion from automatic to manual operation without the use of tools
- Infinitely variable adjustment of rind thickness depending on the product
- Individual positioning of the machine by lockable guide rolls
- The divided hood allows easy handling as it can be removed completely for manual derinding of round cuts.
- Quick and easy cleaning for optimum hygiene (p.e. machine closed from the bottom, no screws in the food area, even surfaces)
- Machine housing in up to 3 mm stainless steel, thus robust and durable

